

View Online at <https://aerobasegroup.com/nsn/6625-01-225-7010>

Circuit Current For Which Designed:

Dc

Overall Length:

3.080 inches

Overall Height:

0.760 inches

Overall Width:

2.410 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and shock resistant and submersible and vibration resistant

Indicator Type:

Digital display

Installation Design:

Panel

Meter Depth Behind Mounting Flange:

2.330 inches

Meter Body Width Behind Mounting Flange:

2.250 inches

Background Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp

Display Type:

Light emitting diode (I.E.D.).

Display Digit Quantity:

3-1/2

Measurement Range:

-19.99 to 19.99 volts, dc single indicator single range

Meter Body Height Behind Mounting Flange:

0.610 inches

Features Provided:

Magnetic shield and overranging and warning feature

Accuracy Rating:

Porm 0.1 pct of reading porm 0.05 pct full scale single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

1 printed circuit

Operating Voltage Rating In Volts:

5.0 ac

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Tested and qualified in accordance w/velonex procedure sv-20567

Style Designator:

Rectangular flush mtg

Supplementary Features:

Internal automatic zero circuit calibration

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0