

View Online at <https://aerobasegroup.com/nsn/6625-01-226-3538>

Circuit Current For Which Designed:

Dc

Overall Length:

2.260 inches

Mounting Hole Diameter:

0.157 inches

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

30.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.310 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Electrodynamometer

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0 to 1.0 watts single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Knife edge pointer and magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Annular; low flux

Material:

Plastic phenol-formaldehyde or plastic polycarbonate

Special Test Features:

Meter must be critically damped w/source impedance of 30 ko

Style Designator:

C1 round flush mtg

Supplementary Features:

1400 ohms internal res

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0