

View Online at <https://aerobasegroup.com/nsn/6625-01-226-3538>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.260 inches

**Mounting Hole Diameter:**

0.157 inches

**Overall Diameter:**

3.500 inches

**Mounting Bolt Circle Diameter:**

3.160 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Sensitivity Rating:**

30.0 microamperes

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.310 inches

**Meter Body Diameter Behind Mounting Flange:**

2.750 inches

**Movement Type:**

Electrodynamometer

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

+0.0 to 1.0 watts single indicator 1st range

**Scale Selection Method:**

Terminal

**Features Provided:**

Knife edge pointer and magnetic shield and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Annular; low flux

**Material:**

Plastic phenol-formaldehyde or plastic polycarbonate

**Special Test Features:**

Meter must be critically damped w/source impedance of 30 ko

**Style Designator:**

C1 round flush mtg

**Supplementary Features:**

1400 ohms internal res

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0