

View Online at <https://aerobasegroup.com/nsn/6625-01-227-4370>

**Circuit Current For Which Designed:**

Ac

**Overall Depth:**

110.0 millimeters

**Overall Length:**

243.0 millimeters

**Overall Width:**

158.0 millimeters

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**End Application:**

Electronic test equipment

**Indicator Type:**

Digital display

**Installation Design:**

Bench or hand held

**Power Source:**

Internal

**Display Type:**

Light emitting diode

**Display Digit Quantity:**

3-1/2

**Measurement Range:**

+0.5 to 2300.0 megahertz single indicator single range

**Accuracy Rating:**

Porm 5 pct of full scale cw single indicator single range

**Display Color:**

Amber single indicator single range

**Circuit Attachment Method And Quantity:**

2 quick disconnect, female

**Operating Voltage Rating In Volts:**

Between 115.0 ac and 260.0 ac

**Phase:**

Single

**Special Features:**

Voltage ranges are: 115.0/130.0 vac and 230.0/260.0 vac; power range: 100 mw to 10 kw full scale; freq. Range: 450 khz to 2.3 ghz; sampling rate: 2 to 3 readings per second; modulation freq.: 25 to 100000 hz; min. Pulse width: 0.8 usec; min. Rep rate: 25 pps; min. Duty cycle: 0.01 pct; impedance: 50ohms; insertion swr: 1.05 max. To 1000 mhz; rechargeable battery with 8 hour life; front panel finish: laminate polycarbonate; lower housing: clear anaodize; has 7 ft power cord

**Functional Description:**

Rf power analyst

**Reference Data And Literature:**

T.O.33a1-7-322-1

**Style Designator:**

Hand-held

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0