

View Online at <https://aerobasegroup.com/nsn/6625-01-227-4370>

Circuit Current For Which Designed:

Ac

Overall Depth:

110.0 millimeters

Overall Length:

243.0 millimeters

Overall Width:

158.0 millimeters

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

End Application:

Electronic test equipment

Indicator Type:

Digital display

Installation Design:

Bench or hand held

Power Source:

Internal

Display Type:

Light emitting diode

Display Digit Quantity:

3-1/2

Measurement Range:

+0.5 to 2300.0 megahertz single indicator single range

Accuracy Rating:

Porm 5 pct of full scale cw single indicator single range

Display Color:

Amber single indicator single range

Circuit Attachment Method And Quantity:

2 quick disconnect, female

Operating Voltage Rating In Volts:

Between 115.0 ac and 260.0 ac

Phase:

Single

Special Features:

Voltage ranges are: 115.0/130.0 vac and 230.0/260.0 vac; power range: 100 mw to 10 kw full scale; freq. Range: 450 khz to 2.3 ghz; sampling rate: 2 to 3 readings per second; modulation freq.: 25 to 100000 hz; min. Pulse width: 0.8 usec; min. Rep rate: 25 pps; min. Duty cycle: 0.01 pct; impedance: 50ohms; insertion swr: 1.05 max. To 1000 mhz; rechargeable battery with 8 hour life; front panel finish: laminate polycarbonate; lower housing: clear anaodize; has 7 ft power cord

Functional Description:

Rf power analyst

Reference Data And Literature:

T.O.33a1-7-322-1

Style Designator:

Hand-held

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0