

View Online at <https://aerobasegroup.com/nsn/6625-01-228-3113>

Circuit Current For Which Designed:

Dc

Overall Length:

2.310 inches

Scale Division Quantity:

2 single indicator single range

Mounting Stud Length:

0.910 inches

Overall Diameter:

2.300 inches

Environmental Protection:

Watertight

Distance Between Mounting Facility Centers:

1.500 inches

Furnished Items And Quantity:

Mtg hdw 2; term. Hdw 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

60.0 amperes

Dial Scale Marking Color:

Green and red single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.430 inches

Meter Body Diameter Behind Mounting Flange:

2.070 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Scale Marking:

Red and green sections only markings

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Mounting Stud Diameter:

0.164 inches

Features Provided:

Self-illumination facility

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

3 threaded stud

Special Features:

One terminal for ground to mtg stud

Special Markings:

Red from m 60 amp to 0 amp and green from 0 amp to 60 amp deflections

Material:

Plastic or stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Bezel sealed with rubber gasket

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0