

View Online at <https://aerobasegroup.com/nsn/6625-01-229-8845>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

2.480 inches

Overall Height:

2.702 inches

Overall Width:

2.702 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.500 inches

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.252 inches

Meter Body Diameter Behind Mounting Flange:

2.180 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 500.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Shunt rated

Special Test Features:

Meets ansi specification c-39.1

Style Designator:

Rectangular flush mtg

Supplementary Features:

12.5 ohms terminal resistance

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0