

View Online at <https://aerobasegroup.com/nsn/6625-01-230-9175>

Reliability Indicator:

Not established

Mounting Provision Quantity:

2

Overall Length:

Between 5.970 inches and 6.030 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 5.240 inches and 5.260 inches

Overall Height:

Between 1.330 inches and 1.430 inches

Overall Width:

Between 1.220 inches and 1.280 inches

Unthreaded Mounting Hole Diameter:

Between 0.185 inches and 0.215 inches

Furnished Items And Quantity:

Screw 2; flat washer 4

Usage Design:

External

Accuracy In Percent:

-0.25 to 0.25 all ranges

Element Material:

Manganese

Mounting Method:

Unthreaded hole

Cubic Measure:

11.037 cubic inches

Terminal Location:

Top

Voltage Drop In Millivolts:

50.0

Current Rating And Type:

75.0 amperes dc

Special Features:

0.468 in. Diameter counterbore on mtg holes

Special Test Features:

Interpret drawing iaw dod-std-100c; shock iaw mil-std-202; mark iaw mil-std-130

Supplementary Features:

Dielectric strength 1500 v rms

Terminal Type And Quantity:

2 threaded stud

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A33500