

View Online at <https://aerobasegroup.com/nsn/6625-01-230-9175>

**Reliability Indicator:**

Not established

**Mounting Provision Quantity:**

2

**Overall Length:**

Between 5.970 inches and 6.030 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 5.240 inches and 5.260 inches

**Overall Height:**

Between 1.330 inches and 1.430 inches

**Overall Width:**

Between 1.220 inches and 1.280 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.185 inches and 0.215 inches

**Furnished Items And Quantity:**

Screw 2; flat washer 4

**Usage Design:**

External

**Accuracy In Percent:**

-0.25 to 0.25 all ranges

**Element Material:**

Manganese

**Mounting Method:**

Unthreaded hole

**Cubic Measure:**

11.037 cubic inches

**Terminal Location:**

Top

**Voltage Drop In Millivolts:**

50.0

**Current Rating And Type:**

75.0 amperes dc

**Special Features:**

0.468 in. Diameter counterbore on mtg holes

**Special Test Features:**

Interpret drawing iaw dod-std-100c; shock iaw mil-std-202; mark iaw mil-std-130

**Supplementary Features:**

Dielectric strength 1500 v rms

**Terminal Type And Quantity:**

2 threaded stud

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A33500