

View Online at <https://aerobasegroup.com/nsn/6625-01-232-1339>

Circuit Current For Which Designed:

Dc

Overall Length:

2.070 inches

Mounting Stud Length:

0.570 inches

Overall Diameter:

2.300 inches

Distance Between Mounting Facility Centers:

1.320 inches

Furnished Items And Quantity:

Mtg hdw 2; term. Hdw 2; gasket 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Green and red and white single indicator single range

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.230 inches

Meter Body Diameter Behind Mounting Flange:

2.060 inches

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+10.0 to 16.0 volts single indicator single range

Mounting Stud Diameter:

0.190 inches

Scale Selection Method:

Terminal

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Batt chg; bands: red from 8 to 11.3 and from 15.3 to 18; white from 11.3 to 12; green from 12 to 12.8 and from 13.3 to 15.3 volts

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Dichromate and zinc

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0