

View Online at <https://aerobasegroup.com/nsn/6625-01-232-1339>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.070 inches

**Mounting Stud Length:**

0.570 inches

**Overall Diameter:**

2.300 inches

**Distance Between Mounting Facility Centers:**

1.320 inches

**Furnished Items And Quantity:**

Mtg hdw 2; term. Hdw 2; gasket 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Dial Scale Marking Color:**

Green and red and white single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.230 inches

**Meter Body Diameter Behind Mounting Flange:**

2.060 inches

**Background Color:**

Black single indicator single range

**Pointer Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 clamp and 2 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+10.0 to 16.0 volts single indicator single range

**Mounting Stud Diameter:**

0.190 inches

**Scale Selection Method:**

Terminal

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Markings:**

Batt chg; bands: red from 8 to 11.3 and from 15.3 to 18; white from 11.3 to 12; green from 12 to 12.8 and from 13.3 to 15.3 volts

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Dichromate and zinc

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0