

View Online at <https://aerobasegroup.com/nsn/6625-01-233-0682>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.312 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Mounting Hole Diameter:**

0.125 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Furnished Items And Quantity:**

Term. Hdw 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Green single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

Green section only mark

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

Green band from 36.0 to 54.0 degrees deflection

**Material:**

Steel

**Surface Treatment:**

Enamel

**Special Test Features:**

Meets mil-m-10304 requirements

**Style Designator:**

Rectangular flush mtg

**Specification Data:**

55910-0008817 manufacturers specification control

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0