

View Online at <https://aerobasegroup.com/nsn/6625-01-233-2343>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

5.688 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.375 inches

**Overall Height:**

4.312 inches

**Overall Width:**

4.312 inches

**Mounting Stud Length:**

0.625 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+50.000 to 60.000 hertz

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0 to 1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

5.187 inches

**Meter Body Diameter Behind Mounting Flange:**

3.969 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.5 to 5.0 power factor single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Movement Suspension Method:**

Metal pivot base

**Circuit Attachment Method And Quantity:**

3 threaded stud

**Phase:**

Three

**Special Features:**

Ruggedized

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Complies with ansi specification c-39.1

**Style Designator:**

Rectangular flush mtg

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0