

View Online at <https://aerobasegroup.com/nsn/6625-01-233-4436>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

2.590 inches

**Mounting Hole Diameter:**

0.150 inches

**Overall Diameter:**

4.600 inches

**Environmental Protection:**

Watertight

**Mounting Bolt Circle Diameter:**

4.125 inches

**Furnished Items And Quantity:**

Nut 6; washer 6; o ring 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Six hole/stud bolt circle

**Sensitivity Rating:**

1.0 milliamperes

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

1.440 inches

**Meter Body Diameter Behind Mounting Flange:**

3.650 inches

**Movement Type:**

Moving coil, permanent magnet

**Power Source:**

External

**Mounting Facility Type And Quantity:**

6 screw and 6 unthreaded hole

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Material:**

Steel

**Surface Treatment:**

Cadmium and chromate

**Style Designator:**

C1 round flush mtg

**Supplementary Features:**

Self shielding movement suspension

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A310a0