NSN 6625-01-233-8498

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-233-8498

| Circuit Curren | For Which | Designed: |
|----------------|-----------|-----------|
|----------------|-----------|-----------|

Dc

Overall Length:

2.750 inches

Scale Division Quantity:

80 single indicator single range

Mounting Stud Length:

0.500 inches

Overall Diameter:

3.950 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.593 inches

Furnished Items And Quantity:

Mtg hdw 3; term. Hdw 2; o ring 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.920 inches

Meter Body Diameter Behind Mounting Flange:

3.100 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Rpm; 0; 1000; 2000; 3000; 4000; 5000; 6000; 7000; 8000

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

NSN 6625-01-233-8498

Special Scale Meter - Page 2 of 2



| Mounting Stud Diameter: | | |
|---|--|--|
| 0.190 inches | | |
| Features Provided: | | |
| Zero adjuster | | |
| Circuit Attachment Method And Quantity: | | |
| 2 threaded stud | | |
| Special Features: | | |
| Ruggedized | | |
| Nuclear Hardness Critical Feature: | | |
| Nonhardened | | |
| Style Designator: | | |
| Round flush mtg | | |
| Fsc Application Data: | | |
| Test set, elect. Equip. | | |
| Shelf Life: | | |
| N/a | | |
| Unit Of Measure: | | |
| | | |
| Demilitarization: | | |
| No | | |
| Fiig: | | |
| A310a0 | | |