# NSN 6625-01-234-4496

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-234-4496

#### **Circuit Current For Which Designed:**

Dc

**Overall Length:** 

11.000 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 3.346 inches and 3.406 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.346 inches and 3.406 inches

**Overall Height:** 

Between 4.250 inches and 4.750 inches

**Overall Width:** 

Between 4.250 inches and 4.750 inches

**Scale Division Quantity:** 

60 single indicator single range

**Mounting Stud Length:** 

Between 0.500 inches and 0.750 inches

**Environmental Protection:** 

Shock resistant and vibration resistant

**End Application:** 

Cont panel

# **Furnished Items And Quantity:**

Nut 12; washer 4

**Indicator Type:** 

Dial w/pointer

#### **Installation Design:**

Panel

# **Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:** 

1.0 milliamperes

#### **Dial Scale Marking Color:**

Black single indicator single range

#### **Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

#### **Meter Depth Behind Mounting Flange:**

9.000 inches

## **Meter Body Diameter Behind Mounting Flange:**

3.980 inches

### **Movement Type:**

Moving coil, permanent magnet

#### **Background Color:**

White single indicator single range

# NSN 6625-01-234-4496

Special Scale Meter - Page 2 of 2



Pointer Color:
Black single indicator single range
Scale Marking:
Inches hg; psi; 30, 20, 10, 0, 10, 20, 30; heavy black line at 0 with arrow pointing left for inches hg, arrow pointingright for ps
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Mounting Stud Diameter:
0.250 inches
Features Provided:
Magnetic shield
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Conforms to mil-m-16034/2 type mr49w001spech
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Electrical, electronic properties measuring and test instruments
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A310a0