

View Online at <https://aerobasegroup.com/nsn/6625-01-235-8765>

Circuit Current For Which Designed:

Dc

Overall Length:

1.355 inches

Overall Height:

1.640 inches

Overall Width:

1.980 inches

Mounting Stud Length:

0.500 inches

Distance Between Mounting Facility Centers:

1.250 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges and red single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

0.820 inches

Meter Body Diameter Behind Mounting Flange:

1.100 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-20.0/+3.0 voice units single indicator 1st range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Knife edge pointer and magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

225 ohm resistance

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Fan shape flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0