

View Online at <https://aerobasegroup.com/nsn/6625-01-236-6388>

**Overall Length:**

17.500 inches

**Overall Height:**

5.400 inches

**Overall Width:**

13.200 inches

**Current Type:**

Ac or dc

**Frequency Rating:**

Between 40.0 hertz and 440.0 hertz

**End Application:**

5825-00-128-3195, beacon transponder, an/trn-26

**Voltage Rating:**

100.0 volts and 220.0 volts and 220.0 volts and 240.0 volts

**Beam Quantity:**

1

**Graduation Interval:**

Graduated in. V/div on y-axis; graduated in. Time/div on x-axis

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Included

**Sweep Circuit Type:**

Horizontal and vertical

**Sweep Frequency Range:**

+0.0/+100.0 megahertz

**Single Trigger Sweep Duration:**

Between 0.00005 microseconds and 500000.0 microseconds

**Trigger Sweep Voltage Amplitude Rating:**

Between 100.0 megavolts and 300.0 megavolts

**Trigger Sweep Polarity Switch:**

Included

**Trigger Sweep Marker Intervals:**

0.5 second and 50 nanosecond

**Expanded Sweep:**

Provided

**Amplifier Deflection Sensitivity Provision:**

Not provided

**Input Intensity Modulation Feature:**

Provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Provided

**Frequency Response Rating:**

Provided

**Amplifier Input Impedance Rating Provision:**

Not provided

**Calibrated Screen Scale:**

Included

**Trace Storage Tube:**

Included

**Camera Recording Device Accommodation:**

Not provided

**Phase:**

Single

**Special Features:**

Transit case provided

**Supplementary Features:**

Oper. Alt. 15000.0 ft.; oper.Tempm10.0 to p55.0 deg. C; p31 phosphor standard; dc voltage rating 20.0-32.0

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-g