

View Online at <https://aerobasegroup.com/nsn/6625-01-236-6388>

Overall Length:

17.500 inches

Overall Height:

5.400 inches

Overall Width:

13.200 inches

Current Type:

Ac or dc

Frequency Rating:

Between 40.0 hertz and 440.0 hertz

End Application:

5825-00-128-3195, beacon transponder, an/trn-26

Voltage Rating:

100.0 volts and 220.0 volts and 220.0 volts and 240.0 volts

Beam Quantity:

1

Graduation Interval:

Graduated in. V/div on y-axis; graduated in. Time/div on x-axis

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+0.0/+100.0 megahertz

Single Trigger Sweep Duration:

Between 0.00005 microseconds and 500000.0 microseconds

Trigger Sweep Voltage Amplitude Rating:

Between 100.0 megavolts and 300.0 megavolts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

0.5 second and 50 nanosecond

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Not provided

Input Intensity Modulation Feature:

Provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Frequency Response Rating:

Provided

Amplifier Input Impedance Rating Provision:

Not provided

Calibrated Screen Scale:

Included

Trace Storage Tube:

Included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Special Features:

Transit case provided

Supplementary Features:

Oper. Alt. 15000.0 ft.; oper.Tempm10.0 to p55.0 deg. C; p31 phosphor standard; dc voltage rating 20.0-32.0

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g