

View Online at <https://aerobasegroup.com/nsn/6625-01-236-9458>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

7.980 inches

Overall Height:

2.035 inches

Overall Width:

3.875 inches

Frequency Rating:

Between 0.047 kilohertz and 1.200 kilohertz

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Seal 1

Indicator Type:

Digital display

Installation Design:

Panel

Frequency Response Range:

+0.047/+1.200 kilohertz

Sensitivity Rating:

115.0 volts

Dial Scale Marking Color:

White single indicator single range

Meter Depth Behind Mounting Flange:

7.290 inches

Meter Body Width Behind Mounting Flange:

3.594 inches

Background Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bezel and 1 plug-in

Display Type:

Light emitting diode

Display Digit Quantity:

5-1/2

Measurement Range:

+47.0/+1200.0 hertz single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.740 inches

Features Provided:

Magnetic shield

Accuracy Rating:

Porm 0.05 pct of one digit single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

1 printed circuit

Operating Voltage Rating In Volts:

115.0 ac

Phase:

Single

Special Features:

Ruggedized

Special Markings:

Number each pin o back, 1 to 16

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0