NSN 6625-01-238-0880

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-238-0880

Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
0.125 inches
Overall Diameter:
2.695 inches
Environmental Protection:
Cold resistant and fungus resistant and heat resistant and humidity resistant and salt spray resistant and shock resistant and vibration
resistant and watertight
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Mtg hdw 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+50.000/+1000.000 hertz
Sensitivity Rating:
1000.0 ohms per volt
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-3.0/+3.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.050 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range

Pointer Color:Black single indicator single range

NSN 6625-01-238-0880

Voltmeter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Measurement Range:
+0.0/+150.0 volts, ac single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 binding post
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Cadmium and chromate
Style Designator:
Round flush mtg
Supplementary Features:
150 ko resistance
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0