## NSN 6625-01-239-1802

Voltmeter - Page 1 of 2

Moving coil, permanent magnet



View Online at https://aerobasegroup.com/nsn/6625-01-239-1802

view Offiline at https://aerobasegroup.com/nsn/0025-01-255-1002
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
2600.0
Overall Length:
2.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.250 inches
Overall Height:
3.250 inches
Overall Width:
3.250 inches
Scale Division Quantity:
60 single indicator all ranges
Mounting Stud Length:
0.500 inches
Environmental Protection:
Cold resistant and fungus proof and heat resistant and humidity resistant and salt spray resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Term. Hdw 2; mtg hdw 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.230 inches
Meter Body Diameter Behind Mounting Flange:
2.690 inches
Movement Type:

## NSN 6625-01-239-1802

Voltmeter - Page 2 of 2



Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
+0.0/+7.5 kilovolts, dc single indicator 1st range
Mounting Stud Diameter:
0.112 inches
Scale Selection Method:
Terminal
Features Provided:
Knife edge pointer and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to ansi c39.1-1972
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A310a0