

View Online at <https://aerobasegroup.com/nsn/6625-01-240-6691>

Overall Depth:

12.500 inches

Overall Height:

4.625 inches

Overall Width:

9.125 inches

Current Type:

Ac and dc

Direct Current Rating In Amps:

800.0

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Accessory Components And Quantity:

Instruction manual 1; Ip-16ax switchable x1/x10 probes 2; ac power cable 1; viewing hood, lh-2008 1; dc powercable 1; Ip-2054 battery pack 1

Voltage Rating:

Between 100.0 volts and 234.0 volts

Screen Size:

3 by 3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Amplifier Deflection Sensitivity Provision:

Provided

Horizontal Deflection Sensitivity Voltage Rating:

1.0 volts any acceptable major

Input Intensity Modulation Feature:

Provided

Visual Modulation Sensitivity Voltage Rating:

2.0 millivolts

Amplifier Input Impedance Rating Provision:

Provided

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

0.1 volts

Calibrated Screen Scale:

Included

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-g