

View Online at <https://aerobasegroup.com/nsn/6625-01-243-3603>

Circuit Current For Which Designed:

Dc

Overall Length:

3.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.422 inches

Overall Width:

4.422 inches

Mounting Hole Diameter:

0.313 inches

Scale Division Quantity:

60 single indicator single range

Environmental Protection:

Corrosion resistant and shock resistant

Furnished Items And Quantity:

Mtg hdw 4; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5/+1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.876 inches

Meter Body Diameter Behind Mounting Flange:

3.960 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-3000.0/+3000.0 amperes, dc single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets requirements of mil-w-19088; tested under mil-s-901

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0