NSN 6625-01-245-6779

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-245-6779
Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
2600.0
Overall Length:
4.437 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.375 inches
Overall Height:
4.422 inches
Overall Width:
4.422 inches
Mounting Hole Diameter:
0.313 inches
Frequency Rating:
Between 60.0 hertz and 400.0 hertz
Environmental Protection:
Corrosion resistant and shock resistant
Furnished Items And Quantity:
Term. Hdw 2; mtg hdw 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.5/+1.5 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
3.188 inches
Meter Body Diameter Behind Mounting Flange:
3.960 inches
Movement Type:
Moving iron vane
Background Color:
White single indicator single range

Pointer Color:

Black single indicator single range

NSN 6625-01-245-6779

Ammeter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator single range
Measurement Range:
+0.0/+1000.0 amperes, ac single indicator single range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Phase:
Single
Special Features:
Ruggedized
Special Markings:
Red mark at 800 amp
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Special Test Features:
Conforms to mil-m-16034
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0