## NSN 6625-01-245-6782

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-245-6782

| Circuit Current For Which Designed:                                       |
|---|
| Dc  |
| Dielectric Withstanding Voltage In Volts:                                 |
| 2600.0  |
| Overall Length:   |
| 4.063 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.376 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 3.376 inches  |
| Overall Height:   |
| 4.422 inches  |
| Overall Width:  |
| 4.422 inches  |
| Mounting Hole Diameter:   |
| 0.312 inches  |
| Scale Division Quantity:  |
| 100 single indicator single range   |
| Environmental Protection:   |
| Shock resistant   |
| Furnished Items And Quantity:   |
| Mtg hdw 4; term. Hdw2   |
| Indicator Type:   |
| Dial w/pointer  |
| Installation Design:  |
| Panel   |
| Mounting Arrangement Style:   |
| Four hole/stud rectangular/square   |
| Sensitivity Rating:   |
| 1.0 milliamperes  |
| Dial Scale Marking Color:   |
| Black single indicator single range                                       |
| Accuracy In Percent:  |
| -1.5/+1.5 at full scale single indicator single range                     |
| Meter Depth Behind Mounting Flange:                                       |
| 2.813 inches  |
| Meter Body Diameter Behind Mounting Flange:                               |
| 3.960 inches  |
| Movement Type:  |
| Moving coil, permanent magnet   |
| Background Color:   |

White single indicator single range

## NSN 6625-01-245-6782

Special Scale Meter - Page 2 of 2



| Pointer Color:  |
|---|
| Black single indicator single range   |
| Scale Marking:  |
| nches; level; 0; 50; 100; 150; 200  |
| Mounting Facility Type And Quantity:  |
| 4 screw and 4 unthreaded hole   |
| Scale Graduation Type:  |
| Linear single indicator single range  |
| Features Provided:  |
| Zero adjuster   |
| Criticality Code Justification:   |
| Zzzy  |
| Movement Suspension Method:   |
| Taut band   |
| Circuit Attachment Method And Quantity:   |
| 2 threaded stud   |
| Material:   |
| Plastic   |
| Nuclear Hardness Critical Feature:  |
| Nonhardened   |
| Special Test Features:  |
| Conforms to mil-m-16034   |
| Style Designator:   |
| Rectangular flush mtg   |
| Supplementary Features:   |
| Ruggedized  |
| Fsc Application Data:   |
| Test set, elect. Equip.   |
| Reference Number Differentiating Characteristics:   |
| Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testingtesting specifications |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| -   |
| Demilitarization:   |
| Yes - demil/mli   |
| Filg:   |
| <b>4</b> 310a0  |
|   |