## NSN 6625-01-246-8716

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-246-8716

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
800.0
Overall Length:
4.063 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.375 inches
Overall Height:
4.422 inches
Overall Width:
4.422 inches
Mounting Hole Diameter:
0.312 inches
Scale Division Quantity:
100 single indicator single range
Environmental Protection:
Corrosion resistant and shock resistant
Furnished Items And Quantity:
Mtg hdw 4; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.5/+1.5 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.813 inches
Meter Body Diameter Behind Mounting Flange:
3.960 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single regard

Black single indicator single range

## NSN 6625-01-246-8716

Special Scale Meter - Page 2 of 2

N/a

--



## **Scale Marking:** Inches level; 0; 50; 100; 150; 200 Mounting Facility Type And Quantity: 4 screw and 4 unthreaded hole Scale Graduation Type: Linear single indicator single range **Features Provided:** Zero adjuster **Criticality Code Justification:** Zzzy **Movement Suspension Method:** Taut band **Circuit Attachment Method And Quantity:** 2 threaded stud **Special Features:** Item must comply with requirements of defense supply center columbus production standard no. Lo3589 Material: Plastic **Special Test Features:** Conforms to mil-m-16034 **Style Designator:** Rectangular flush mtg **Supplementary Features:** Ruggedized **Fsc Application Data:** Test set, elect. Equip. **Reference Number Differentiating Characteristics:** Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp Shelf Life: Unit Of Measure: **Demilitarization:** Yes - demil/mli Fiig: A310a0