# NSN 6625-01-247-9280

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-247-9280

# Circuit Current For Which Designed:

Ac

# Dielectric Withstanding Voltage In Volts:

2000.0

# **Overall Length:**

5.390 inches

### Center To Center Distance Between Mounting Facilities Parallel To Length:

#### 3.390 inches

## Center To Center Distance Between Mounting Facilities Parallel To Width:

3.390 inches

#### **Overall Height:**

4.330 inches

#### **Overall Width:**

4.330 inches

#### Scale Division Quantity:

#### 25 single indicator single range

Mounting Stud Length:

#### 0.620 inches

## **Environmental Protection:**

Airtight and dust resistant and fungus resistant and humidity resistant and salt water resistant and shock resistant and vibration resistant and water resistant

#### **Furnished Items And Quantity:**

Nut 8; lockwasher 8

#### Indicator Type:

Dial w/pointer

#### Installation Design:

Panel

#### Mounting Arrangement Style:

Four hole/stud rectangular/square

## Frequency Response Range:

+40.000/+70.000 hertz

#### Sensitivity Rating:

5.0 volts

#### **Dial Scale Marking Color:**

Black single indicator single range

#### Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

#### Unable To Decode:

Unable to decode or unable to decode

#### Meter Depth Behind Mounting Flange:

3.380 inches

## Meter Body Diameter Behind Mounting Flange:

3.940 inches

# NSN 6625-01-247-9280

Voltmeter - Page 2 of 2

A310a0



Movement Type: Moving iron vane **Background Color:** White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:** External Mounting Facility Type And Quantity: 4 threaded stud Scale Graduation Type: Linear single indicator single range **Measurement Range:** +0.0/+5.0 volts, ac single indicator single range **Mounting Stud Diameter:** 0.250 inches **Scale Selection Method:** Terminal **Features Provided:** Knife edge pointer and shatterproof glass and zero adjuster **Movement Suspension Method:** Taut band **Circuit Attachment Method And Quantity:** 2 threaded stud Material: Plastic **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Paint **Special Test Features:** Complies with mil-m-10304 Style Designator: Rectangular flush mtg **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: