NSN 6625-01-251-0112

Multimeter - Page 1 of 2

3000.0

Overall Length:

Circuit Current For Which Designed:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-01-251-0112

2.650 inches
Mounting Hole Diameter:
0.112 inches
Overall Diameter:
2.695 inches
Environmental Protection:
Shock resistant and vibration resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Mtg hdw 3; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 microamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.600 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:
External

NSN 6625-01-251-0112

Multimeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator all ranges
Measurement Range:
-20.0/+2.0 decibels single indicator 1st range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug
Special Features:
Ruggedized
Special Markings:
Green band from 68 to 83 pct of full scale deflection on amp scale
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Special Test Features:
Conforms to mil-m-10304/5, type mr26w100dcuar
Style Designator:
Round flush mtg
Supplementary Features:
150 mv maximum power consumption
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
N310a0