NSN 6625-01-251-0112

Multimeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-251-0112

Circuit Current For Which Designed: Dc **Dielectric Withstanding Voltage In Volts:** 3000.0 **Overall Length:** 2.650 inches Mounting Hole Diameter: 0.112 inches **Overall Diameter:** 2.695 inches **Environmental Protection:** Shock resistant and vibration resistant Mounting Bolt Circle Diameter: 2.440 inches **Furnished Items And Quantity:** Mtg hdw 3; term. Hdw 2 **Indicator Type:** Dial w/pointer Installation Design: Panel Mounting Arrangement Style: Three hole/stud bolt circle **Sensitivity Rating:** 100.0 microamperes **Dial Scale Marking Color:** Black single indicator all ranges Accuracy In Percent: -2.0/+2.0 at full scale single indicator all ranges **Unable To Decode:** Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 1.600 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet **Background Color:** White single indicator all ranges **Pointer Color:** Black single indicator all ranges

Power Source:

External

NSN 6625-01-251-0112

Multimeter - Page 2 of 2



Mounting Facility Type And Quantity: 3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-20.0/+2.0 decibels single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Special Markings:

Green band from 68 to 83 pct of full scale deflection on amp scale

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Special Test Features:

Conforms to mil-m-10304/5, type mr26w100dcuar

Style Designator:

Round flush mtg

Supplementary Features:

150 mv maximum power consumption

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A310a0