NSN 6625-01-251-0113

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-251-0113

Circuit Current For Which Designed:
Dc
Overall Length:
4.715 inches
Overall Height:
1.929 inches
Overall Width:
3.897 inches
Frequency Rating:
60.0 hertz
Environmental Protection:
Humidity resistant
Indicator Type:
Digital display
Installation Design:
Panel
Frequency Response Range:
+50.000/+400.000 hertz
Sensitivity Rating:
100.0 microvolts
Meter Depth Behind Mounting Flange:
Meter Depth Behind Mounting Flange: 4.000 inches
4.000 inches
4.000 inches Meter Body Width Behind Mounting Flange:
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color:
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source:
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity:
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity: 2 clip
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity: 2 clip Display Type:
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity: 2 clip Display Type: Light emitting diode
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity: 2 clip Display Type: Light emitting diode Display Digit Quantity:
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity: 2 clip Display Type: Light emitting diode Display Digit Quantity: 3-1/2
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity: 2 clip Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range:
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity: 2 clip Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range: -199.9/+199.9 milliamperes, dc single indicator single range
4.000 inches Meter Body Width Behind Mounting Flange: 3.590 inches Background Color: Black single indicator single range Power Source: External Mounting Facility Type And Quantity: 2 clip Display Type: Light emitting diode Display Digit Quantity: 3-1/2 Measurement Range: -199.9/+199.9 milliamperes, dc single indicator single range Scale Selection Method:

Features Provided:

Electrical overload protection and overranging

NSN 6625-01-251-0113

Ammeter - Page 2 of 2



Accuracy Rating:
Porm 0.1 pct of reading plus 1 digit single indicator single range
Display Color:
Red single indicator single range
Circuit Attachment Method And Quantity:
1 printed circuit
Operating Voltage Rating In Volts:
120.0 ac
Phase:
Single
Special Features:
Automatic zero
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Supplementary Features:
Porm 0.01 pct of reading plus 0.05 digit temperature coefficient
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0