

View Online at <https://aerobasegroup.com/nsn/6625-01-251-2830>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

800.0

Overall Length:

7.218 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.422 inches

Overall Width:

4.422 inches

Mounting Hole Diameter:

0.313 inches

Frequency Rating:

60.0 hertz

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Mtg hdw 4; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+15.000/+150.000 hertz

Sensitivity Rating:

5.0 amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.750 inches

Meter Body Diameter Behind Mounting Flange:

3.960 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0/+50.0 amperes, ac single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Phase:

Single

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to ansi c39.1

Style Designator:

Rectangular flush mtg

Supplementary Features:

4.0 in. For 100 degrees scale lg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0