NSN 6625-01-251-2833

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-251-2833

| Circuit Current For Which Designed: |
|---|
| Dc |
| Dielectric Withstanding Voltage In Volts: |
| 2600.0 |
| Overall Length: |
| 3.500 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.375 inches |
| Overall Height: |
| 4.423 inches |
| Overall Width: |
| 4.423 inches |
| Mounting Hole Diameter: |
| 0.313 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Environmental Protection: |
| Corrosion resistant and shock resistant and vibration resistant |
| Furnished Items And Quantity: |
| Mtg hdw 4; term. Hdw 2 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 1.0 milliamperes |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.5/+1.5 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.251 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.960 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |

White single indicator single range

NSN 6625-01-251-2833

Special Scale Meter - Page 2 of 2



| Pointer Color: |
|--|
| Black single indicator single range |
| Scale Marking: |
| Psig pressure; 0; 500; 1000; 1500; 2000; 2500 |
| Mounting Facility Type And Quantity: |
| 4 screw and 4 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |
| Features Provided: |
| Magnetic shield and zero adjuster |
| Criticality Code Justification: |
| Zzzy |
| Movement Suspension Method: |
| Taut band |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| Item must comply w/requirements of defense supply center columbus production standard no. Lo3656 |
| Material: |
| Plastic |
| Special Test Features: |
| Conforms to mil-m-16034 |
| Style Designator: |
| Rectangular flush mtg |
| Supplementary Features: |
| Ruggedized; plate id klh2236ab |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Reference Number Differentiating Characteristics: |
| Reference number differentiating material will be iaw naval inventory control point activity hx quality control; manufacturing and testing |
| specifications available at the dla icp |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |
| |