

View Online at <https://aerobasegroup.com/nsn/6625-01-251-3437>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

7.496 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.050 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.725 inches

**Overall Height:**

1.520 inches

**Overall Width:**

6.690 inches

**Mounting Hole Diameter:**

0.221 inches

**Scale Division Quantity:**

25 single indicator single range

**Environmental Protection:**

Humidity resistant and shock resistant and vibration resistant

**Furnished Items And Quantity:**

Nut 8; washer 8; gasket 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

20.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

5.760 inches

**Meter Body Width Behind Mounting Flange:**

5.435 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Red single indicator single range

**Scale Marking:**

Feet b surf; 0; .5; 1; 1.5; 2; 2.5

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Meter Body Height Behind Mounting Flange:**

1.225 inches

**Features Provided:**

Self-illumination facility and zero adjuster

**Criticality Code Justification:**

Astw

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 threaded stud

**Special Features:**

Two term. For lamps

**Special Markings:**

Term. Marked + or -

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Conforms to mil-m-24359

**Style Designator:**

Rectangular flush mtg

**Supplementary Features:**

Vertical mount

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0