NSN 6625-01-251-4533

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-251-4533

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
2600.0
Overall Length:
3.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.375 inches
Overall Height:
4.423 inches
Overall Width:
4.423 inches
Mounting Hole Diameter:
0.313 inches
Scale Division Quantity:
50 single indicator single range
Environmental Protection:
Corrosion resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Mtg hdw 4; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color: Black single indicator single range
Accuracy In Percent:
-1.5/+1.5 at full scale single indicator single range Meter Depth Behind Mounting Flange:
2.251 inches
Meter Body Diameter Behind Mounting Flange:
3.960 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
אירווני אוועוים וויטולמנטו אוועוים ומוועים

NSN 6625-01-251-4533

Special Scale Meter - Page 2 of 2



Pointer Color:

Black single indicator single range

Scale Marking:

Psig pressure; 0; 500; 1000; 1500; 2000; 2500

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Criticality Code Justification:

Feat

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Item must comply w/requirements of desc production standard no. L03657; for navy nuclear propulsion plant products only

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-16034

Style Designator:

Rectangular flush mtg

Supplementary Features:

Ruggedized; plate id klh2236al

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A310a0