## NSN 6625-01-252-0298

Power Factor Meter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-252-0298

Acc Overall Depth: 8.400 inches Overall Height: 3.500 inches Overall Width: 16.800 inches Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, 1i-6310.27, fa-10078, asr-9 system, rms unit 3, section, type; particularly asr-10078, unit 3 (rms); reference data, 3m2, 1i-6310.27, fa-10078, asr-9 system, rms unit 3, section, type; particularly asr-10078, unit 3 (rms); reference data, 3m2, 1i-6310.27, fa-10078, asr-9 system, rms unit 3, section, type; particularly asr-100, pg 8-14 Indicator Type: Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: 40.1/1-2500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable with view handle Shelf Life: N/a Unit of Measure:	Circuit Current For Which Designed:
Overall Depth: 8.400 inches Overall Height: 3.500 inches Overall Height: 3.500 inches Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, section part of the state of	
8.400 inches Overall Height: 3.500 inches Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, sec 1-10, pg 8-14 indicator Type: Digital display installation Design: Rack Display Type: Light emitting diode Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable willt view handle Shelf Life: N/a Unit Of Measure: —— Demilitarization:	
Overall Height: 3.500 inches  Overall Width: 16.800 inches  End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, sec 1-10, pg 8-14 indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4  Measurement Range: +0.11+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	
3.500 inches  Overall Width: 16.800 inches  End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, section, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, section, part of the state of type: Object of	
Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, secti-10, pg 8-14 Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable wiltit view handle Shelf Life: N/a Unit Of Measure: —Demilitarization:	
End Application:  Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, sec 1-10, pg 8-14  Indicator Type: Digital display  Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4  Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a  Unit Of Measure:	
End Application:  Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, sec 1-10, pg 8-14  Indicator Type:  Digital display  Installation Design:  Rack  Display Type:  Light emitting diode  Display Digit Quantity:  4  Measurement Range:  +0.1/+26500.0 megahertz 2nd indicator 2nd range  Accuracy Rating:  Porm 1.2 pct all indicators all ranges  Display Color:  Red all indicators all ranges  Style Designator:  Portable w/tilt view handle  Shelf Life:  N/a  Unit Of Measure:  —Demilitarization:	
Gen-ap-1, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, section, pg 8-14  Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4  Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	
1-10, pg 8-14 Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	
Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	1-10, pg 8-14
Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	Indicator Type:
Rack  Display Type: Light emitting diode  Display Digit Quantity:  4  Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range  Accuracy Rating: Porm 1.2 pct all indicators all ranges  Display Color: Red all indicators all ranges  Style Designator: Portable w/tilt view handle  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	Digital display
Display Type: Light emitting diode Display Digit Quantity:  4  Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	Installation Design:
Light emitting diode  Display Digit Quantity: 4  Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range  Accuracy Rating: Porm 1.2 pct all indicators all ranges  Display Color: Red all indicators all ranges  Style Designator: Portable w/tilt view handle  Shelf Life: N/a  Unit Of Measure:	Rack
Display Digit Quantity:  4  Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pet all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	Display Type:
Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	Light emitting diode
Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	Display Digit Quantity:
+0.1/+26500.0 megahertz 2nd indicator 2nd range  Accuracy Rating: Porm 1.2 pct all indicators all ranges  Display Color: Red all indicators all ranges  Style Designator: Portable w/tilt view handle  Shelf Life: N/a  Unit Of Measure:	4
Accuracy Rating: Porm 1.2 pct all indicators all ranges  Display Color: Red all indicators all ranges  Style Designator: Portable w/tilt view handle  Shelf Life: N/a  Unit Of Measure:	Measurement Range:
Porm 1.2 pct all indicators all ranges  Display Color:  Red all indicators all ranges  Style Designator:  Portable w/tilt view handle  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	+0.1/+26500.0 megahertz 2nd indicator 2nd range
Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure:	Accuracy Rating:
Red all indicators all ranges  Style Designator:  Portable w/tilt view handle  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Porm 1.2 pct all indicators all ranges
Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: Demilitarization:	Display Color:
Portable w/tilt view handle  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Red all indicators all ranges
Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Style Designator:
N/a Unit Of Measure:  Demilitarization:	Portable w/tilt view handle
Unit Of Measure:  Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
Yes - demil/mli	Demilitarization:
	Yes - demil/mli
Fiig:	Fiig:
A310a0	A310a0