NSN 6625-01-252-0298

Power Factor Meter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-01-252-0298

| Acc Overall Depth: 8.400 inches Overall Height: 3.500 inches Overall Width: 16.800 inches Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, 1i-6310.27, fa-10078, asr-9 system, rms unit 3, section, type; particularly asr-10078, unit 3 (rms); reference data, 3m2, 1i-6310.27, fa-10078, asr-9 system, rms unit 3, section, type; particularly asr-10078, unit 3 (rms); reference data, 3m2, 1i-6310.27, fa-10078, asr-9 system, rms unit 3, section, type; particularly asr-100, pg 8-14 Indicator Type: Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: 40.1/1-2500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable with view handle Shelf Life: N/a Unit of Measure: | Circuit Current For Which Designed: |
|---|---|
| Overall Depth: 8.400 inches Overall Height: 3.500 inches Overall Height: 3.500 inches Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, section part of the state of | |
| 8.400 inches Overall Height: 3.500 inches Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, sec 1-10, pg 8-14 indicator Type: Digital display installation Design: Rack Display Type: Light emitting diode Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable willt view handle Shelf Life: N/a Unit Of Measure: —— Demilitarization: | |
| Overall Height: 3.500 inches Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, sec 1-10, pg 8-14 indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.11+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | |
| 3.500 inches Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, section, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, section, part of the state of type: Object of | |
| Overall Width: 16.800 inches End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, secti-10, pg 8-14 Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable wiltit view handle Shelf Life: N/a Unit Of Measure: —Demilitarization: | |
| End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, sec 1-10, pg 8-14 Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | |
| End Application: Gen-ap-t, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, sec 1-10, pg 8-14 Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: —Demilitarization: | |
| Gen-ap-1, typical application: asr9, fa-10078, unit 3 (rms); reference data, 3m2, ti-6310.27, fa-10078, asr-9 system, rms unit 3, section, pg 8-14 Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | |
| 1-10, pg 8-14 Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | |
| Indicator Type: Digital display Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | 1-10, pg 8-14 |
| Installation Design: Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | Indicator Type: |
| Rack Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: Demilitarization: | Digital display |
| Display Type: Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | Installation Design: |
| Light emitting diode Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | Rack |
| Display Digit Quantity: 4 Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pet all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | Display Type: |
| Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | Light emitting diode |
| Measurement Range: +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | Display Digit Quantity: |
| +0.1/+26500.0 megahertz 2nd indicator 2nd range Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | 4 |
| Accuracy Rating: Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | Measurement Range: |
| Porm 1.2 pct all indicators all ranges Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: Demilitarization: | +0.1/+26500.0 megahertz 2nd indicator 2nd range |
| Display Color: Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: | Accuracy Rating: |
| Red all indicators all ranges Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: Demilitarization: | Porm 1.2 pct all indicators all ranges |
| Style Designator: Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: Demilitarization: | Display Color: |
| Portable w/tilt view handle Shelf Life: N/a Unit Of Measure: Demilitarization: | Red all indicators all ranges |
| Shelf Life: N/a Unit Of Measure: Demilitarization: | Style Designator: |
| N/a Unit Of Measure: Demilitarization: | Portable w/tilt view handle |
| Unit Of Measure: Demilitarization: | Shelf Life: |
| Demilitarization: | N/a |
| | Unit Of Measure: |
| | |
| Yes - demil/mli | Demilitarization: |
| | Yes - demil/mli |
| Fiig: | Fiig: |
| A310a0 | A310a0 |
| | |