

View Online at <https://aerobasegroup.com/nsn/6625-01-255-9075>

Circuit Current For Which Designed:

Dc

Overall Length:

3.725 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.900 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.400 inches

Overall Height:

1.750 inches

Overall Width:

1.250 inches

Mounting Hole Diameter:

0.138 inches

Environmental Protection:

Heat resistant and humidity proof

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

21.0 microamperes

Accuracy In Percent:

-0.2/+0.2 at full scale single indicator single range

Movement Type:

Moving iron vane

Mounting Facility Type And Quantity:

4 threaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 wire lead

Operating Voltage Rating In Volts:

Between 11.0 dc and 13.0 dc

Special Features:

Transducer cable to be strain relieved inside case

Material:

Aluminum and steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize

Style Designator:

Rectangular or square

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0