NSN 6625-01-264-2947

Electrical Frequency Meter - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/6625-01-264-2947

| View Online at https://aerobasegroup.com/nsn/6625-01-264-2947 |
|---|
| Circuit Current For Which Designed: |
| Ac |
| Dielectric Withstanding Voltage In Volts: |
| 2600.0 |
| Overall Length: |
| 3.050 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.736 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.370 inches |
| Overall Height: |
| 3.500 inches |
| Overall Width: |
| 3.500 inches |
| Scale Division Quantity: |
| 40 single indicator single range |
| Frequency Rating: |
| 400.0 hertz |
| Mounting Stud Length: |
| 0.530 inches |
| Environmental Protection: |
| Dustproof and splash proof and water resistant |
| Shortest Horizontal Distance Between Mounting Centers: |
| 1.368 inches |
| Furnished Items And Quantity: |
| Gasket 1; nut 9; washer 4 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud triangular |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -3.0/+3.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.610 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.700 inches |

Movement Type:

Moving iron vane

NSN 6625-01-264-2947

Electrical Frequency Meter - Page 2 of 3



| Background Color: |
|---|
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +360.0/+440.0 hertz single indicator single range |
| Mounting Stud Diameter: |
| 0.112 inches |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Taut band |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Operating Voltage Rating In Volts: |
| Between 110.0 ac and 130.0 ac |
| Phase: |
| Single |
| Special Features: |
| 1100 v peak working voltage |
| Material: |
| Plastic |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Supplementary Features: |
| 4.0 va maximum burden |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 6625-01-264-2947

Electrical Frequency Meter - Page 3 of 3



Fiig:

A310a0