

View Online at <https://aerobasegroup.com/nsn/6625-01-266-3969>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

5.560 inches

Overall Height:

1.750 inches

Overall Width:

7.920 inches

Mounting Hole Diameter:

0.160 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Distance Between Mounting Facility Centers:

7.400 inches

Furnished Items And Quantity:

Nut 8; lockwasher 8; shield 1; seal 1

Indicator Type:

Bargraph

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Frequency Response Range:

+58.000/+420.000 hertz

Sensitivity Rating:

20000000.0 ohms

Meter Depth Behind Mounting Flange:

5.130 inches

Meter Body Width Behind Mounting Flange:

6.880 inches

Background Color:

Gray single indicator single range

Scale Marking:

0; 74; pounds x 1000

Mounting Facility Type And Quantity:

2 screw and 2 unthreaded hole

Display Type:

Light emitting diode

Display Digit Quantity:

3

Meter Body Height Behind Mounting Flange:

1.650 inches

Features Provided:

Magnetic shield

Accuracy Rating:

1 pt of reading plus 1 digit single indicator single range

Display Color:

Red single indicator single range

Circuit Attachment Method And Quantity:

6 threaded stud

Special Features:

Ruggedized

Special Markings:

On front, pounds x 1000

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0