

View Online at <https://aerobasegroup.com/nsn/6625-01-266-3969>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Overall Length:**

5.560 inches

**Overall Height:**

1.750 inches

**Overall Width:**

7.920 inches

**Mounting Hole Diameter:**

0.160 inches

**Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

**Distance Between Mounting Facility Centers:**

7.400 inches

**Furnished Items And Quantity:**

Nut 8; lockwasher 8; shield 1; seal 1

**Indicator Type:**

Bargraph

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Frequency Response Range:**

+58.000/+420.000 hertz

**Sensitivity Rating:**

20000000.0 ohms

**Meter Depth Behind Mounting Flange:**

5.130 inches

**Meter Body Width Behind Mounting Flange:**

6.880 inches

**Background Color:**

Gray single indicator single range

**Scale Marking:**

0; 74; pounds x 1000

**Mounting Facility Type And Quantity:**

2 screw and 2 unthreaded hole

**Display Type:**

Light emitting diode

**Display Digit Quantity:**

3

**Meter Body Height Behind Mounting Flange:**

1.650 inches

**Features Provided:**

Magnetic shield

**Accuracy Rating:**

1 pt of reading plus 1 digit single indicator single range

**Display Color:**

Red single indicator single range

**Circuit Attachment Method And Quantity:**

6 threaded stud

**Special Features:**

Ruggedized

**Special Markings:**

On front, pounds x 1000

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0