

View Online at <https://aerobasegroup.com/nsn/6625-01-266-5930>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

355.6 millimeters

**Overall Height:**

148.3 millimeters

**Overall Width:**

425.7 millimeters

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Indicator Type:**

Digital display

**Installation Design:**

Bench

**Frequency Response Range:**

+30.000/+40000.000 megahertz

**Display Type:**

Liquid crystal

**Display Digit Quantity:**

108

**Measurement Range:**

-40.0/+23.0 decibels above or below one milliwatt single indicator all ranges

**Circuit Attachment Method And Quantity:**

Connector, receptacle

**Operating Voltage Rating In Volts:**

Between 100.0 ac and 240.0 ac

**Interface Compatibility:**

ieee-488

**Phase:**

Single

**Special Features:**

Power range m20 to p20 dbm pulse mode and m40 to p20 dbm cw mode; maximum prf greater than 1 mhz; environment 0 to 50 degrees c operating and m40 to p65 degrees c storage; single detector input w/15ns, 18 ghz; memory up to 10 setups; graphic display

**Style Designator:**

Rectangular surface mtg

**Unit Of Issue Weight:**

12.00 kilograms

**Test Data Document:**

81349-mil-t-28800 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Fsc Application Data:**

Lantirn mobility shelter

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0