

View Online at <https://aerobasegroup.com/nsn/6625-01-266-7078>

Circuit Current For Which Designed:

Ac

Overall Length:

11.000 inches

Overall Height:

5.200 inches

Overall Width:

8.400 inches

Frequency Rating:

Between 48.0 hertz and 66.0 hertz and 360.0 hertz and 440.0 hertz

Furnished Items And Quantity:

Hp pn 00730a 5 ft. Cable for power sensor; 7.5 ft. Cable, main plugs

Indicator Type:

Digital display

Installation Design:

Cabinet

Frequency Response Range:

+100.000 to 50000000.000 kilohertz

Power Source:

External

Display Type:

Light emitting diode

Display Digit Quantity:

4

Measurement Range:

-70.0 to 44.0 decibels above or below one milliwatt single indicator single range

Scale Selection Method:

Switch

Features Provided:

Zero adjuster

Accuracy Rating:

Porm 5.0 pct single indicator single range

Operating Voltage Rating In Volts:

100.0 ac and 120.0 ac and 220.0 ac and 240.0 ac

Phase:

Single

Special Features:

Opt 022 is digital input/output, fully compatible w/hp-ib; opt 908 is rack mounting kit; opt 004 is delete power sensor cable

Style Designator:

D1 rectangular or square

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0