

View Online at <https://aerobasegroup.com/nsn/6625-01-267-6590>

Circuit Current For Which Designed:

Dc

Overall Length:

5.875 inches

Overall Height:

1.060 inches

Overall Width:

4.812 inches

Mounting Hole Diameter:

0.156 inches

Frequency Rating:

Between 58.0 hertz and 420.0 hertz

Distance Between Mounting Facility Centers:

4.312 inches

Indicator Type:

Digital display and bargraph

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

200.0 microamperes

Meter Depth Behind Mounting Flange:

5.250 inches

Meter Body Width Behind Mounting Flange:

3.750 inches

Scale Marking:

Pounds x 1000; 0 to 10

Mounting Facility Type And Quantity:

2 screw and 2 unthreaded hole

Display Type:

Light emitting diode

Display Digit Quantity:

3

Meter Body Height Behind Mounting Flange:

0.730 inches

Features Provided:

Overranging and self-illumination facility and warning feature

Accuracy Rating:

Porm 1 pct single indicator single range

Circuit Attachment Method And Quantity:

6 threaded stud

Operating Voltage Rating In Volts:

Between 107.0 ac and 123.0 ac

Special Features:

0 to 5 vrms controls led brightness

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Rectangular flush mtg

Supplementary Features:

Front panel test switch; green under or overrange light

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0