NSN 6625-01-267-6590

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-267-6590

| Circuit Current For Which Designed: |
|--|
| Dc |
| Overall Length: |
| 5.875 inches |
| Overall Height: |
| 1.060 inches |
| Overall Width: |
| 4.812 inches |
| Mounting Hole Diameter: |
| 0.156 inches |
| Frequency Rating: |
| Between 58.0 hertz and 420.0 hertz |
| Distance Between Mounting Facility Centers: |
| 4.312 inches |
| Indicator Type: |
| Digital display and bargraph |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Two hole/stud |
| Sensitivity Rating: |
| 200.0 microamperes |
| Meter Depth Behind Mounting Flange: |
| 5.250 inches |
| Meter Body Width Behind Mounting Flange: |
| 3.750 inches |
| Scale Marking: |
| Pounds x 1000; 0 to 10 |
| Mounting Facility Type And Quantity: |
| 2 screw and 2 unthreaded hole |
| Display Type: |
| Light emitting diode |
| Display Digit Quantity: |
| 3 |
| Meter Body Height Behind Mounting Flange: |
| 0.730 inches |
| Features Provided: |
| Overranging and self-illumination facility and warning feature |
| Accuracy Rating: |
| Porm 1 pct single indicator single range |
| Circuit Attachment Method And Quantity: |
| 6 threaded stud |

NSN 6625-01-267-6590

Special Scale Meter - Page 2 of 2



Operating Voltage Rating In Volts: Between 107.0 ac and 123.0 ac **Special Features:** 0 to 5 vrms controls led brightness Material: Plastic **Nuclear Hardness Critical Feature:** Nonhardened Surface Treatment: Paint Style Designator: Rectangular flush mtg **Supplementary Features:** Front panel test switch; green under or overrange light **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A310a0