NSN 6625-01-269-0980

Ammeter - Page 1 of 2

White single indicator single range



View Online at https://aerobasegroup.com/nsn/6625-01-269-0980

| Circuit Current For Which Designed: |
|---|
| Ac |
| Dielectric Withstanding Voltage In Volts: |
| 800.0 |
| Overall Length: |
| 7.218 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.375 inches |
| Overall Height: |
| 4.422 inches |
| Overall Width: |
| 4.422 inches |
| Mounting Hole Diameter: |
| 0.313 inches |
| Frequency Rating: |
| 60.0 hertz |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Furnished Items And Quantity: |
| Nut 6; washer 12 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 5.0 milliamperes |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -1.0/+1.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 3.750 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 3.960 inches |
| Movement Type: |
| Moving iron vane |
| Background Color: |

NSN 6625-01-269-0980

Ammeter - Page 2 of 2



| Pointer Color: |
|--|
| Black single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 4 screw and 4 unthreaded hole |
| Scale Graduation Type: |
| Nonlinear single indicator single range |
| Measurement Range: |
| +0.0/+1500.0 amperes, ac single indicator single range |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Taut band |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Phase: |
| Single |
| Special Features: |
| Ruggedized |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Special Test Features: |
| Comply w/ansi standards c39.1 |
| Style Designator: |
| Rectangular flush mtg |
| Supplementary Features: |
| Friction resistant |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A310a0 |
| |