

View Online at <https://aerobasegroup.com/nsn/6625-01-269-2463>

Circuit Current For Which Designed:

Ac and dc

Overall Depth:

3.125 inches

Overall Length:

7.000 inches

Overall Width:

5.250 inches

Scale Division Quantity:

50 single indicator 2nd range

Environmental Protection:

Dust resistant and humidity resistant and vibration resistant

Furnished Items And Quantity:

Btry 2; color-coded test leads 2; screw-on clips 2; instruction manual 1

Indicator Type:

Dial w/pointer

Installation Design:

Bench or hand held

Sensitivity Rating:

5.0 kilohm per volt and 20.0 kilohm per volt

Dial Scale Marking Color:

Red single indicator 9th range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator 9th range

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External and internal

Scale Graduation Type:

Nonlinear single indicator 5th range

Scale Selection Method:

Switch and terminal

Features Provided:

Electrical overload protection and internal battery accommodation and internal shunting and mirror scale and portable and rectifier circuit and zero adjuster

Criticality Code Justification:

Matt

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 banana jack and 2 banana plug

Operating Voltage Rating In Volts:

Between 1.5 dc and 9.0 dc

Special Features:

Low power ohms ranges, rx1 0-1k, rx10 0-10k, 0.100 v max; ac amp range use model 150-2 ac amp-clamp adapter; dc ma 4 ranges 0.5/5/50/500; resistance in 4 ranges, rx1/100/1k/10k; ac v 7 ranges 2.5/10/25/100/250/500/1000; dc v 8 ranges 1.0/2.5/10/25/100/250/500/1000; db in 5 ranges.

Special Markings:

Black - sign, red + sign, below bottom scale

Material:

Plastic phenol-formaldehyde

Style Designator:

Portable

Supplementary Features:

Critical application

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0