# NSN 6625-01-269-4139

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-01-269-4139

# Circuit Current For Which Designed:

Dc

# **Overall Length:**

2.310 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

4.000 inches

# Center To Center Distance Between Mounting Facilities Parallel To Width:

3.560 inches

#### **Overall Height:**

3.960 inches

#### **Overall Width:**

5.100 inches

#### Scale Division Quantity:

50 single indicator single range

### **Mounting Stud Length:**

0.500 inches

### **Environmental Protection:**

Cold resistant and dust resistant and fire resistant and heat resistant and humidity resistant and salt spray resistant and sand proof and

shock resistant and vibration resistant

#### Indicator Type:

Dial w/pointer

#### Installation Design:

Panel

#### Mounting Arrangement Style:

Four hole/stud rectangular/square

#### Sensitivity Rating:

500.0 microamperes

### **Dial Scale Marking Color:**

Black single indicator single range

### Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

### Meter Depth Behind Mounting Flange:

1.300 inches

### Meter Body Diameter Behind Mounting Flange:

2.660 inches

## Movement Type:

Moving iron vane

### **Background Color:**

White single indicator single range

### **Pointer Color:**

Black single indicator single range

# Power Source:

External

# NSN 6625-01-269-4139

Ammeter - Page 2 of 2



Mounting Facility Type And Quantity: 1 bezel and 2 screw and 4 threaded stud

# Scale Graduation Type:

Linear single indicator single range

# Measurement Range:

+0.0/+500.0 microamperes, dc single indicator single range

# Mounting Stud Diameter:

0.138 inches

# Scale Selection Method:

Terminal

# **Features Provided:**

Zero adjuster

## **Movement Suspension Method:**

Taut band

#### **Circuit Attachment Method And Quantity:**

2 threaded stud

#### **Special Features:**

Chemical and impact resistant

Material:

Plastic

### **Nuclear Hardness Critical Feature:**

Nonhardened

## **Special Test Features:**

Meets mil-t-945, ul bulletin 94, ansi c39.1

#### **Style Designator:**

Rectangular flush mtg

### Supplementary Features:

Bezel mount

### **Fsc Application Data:**

Test set, elect. Equip.

#### Shelf Life:

N/a

### Unit Of Measure:

---

### Demilitarization:

No

Fiig:

A310a0