

View Online at <https://aerobasegroup.com/nsn/6625-01-270-7070>

Circuit Current For Which Designed:

Dc

Overall Length:

1.700 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

2.980 inches

Overall Width:

3.500 inches

Scale Division Quantity:

5 single indicator single range

Mounting Stud Length:

1.725 inches

Environmental Protection:

Dust tight

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

5.0 volts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.220 inches

Meter Body Diameter Behind Mounting Flange:

2.825 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+5.0 volts, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Moisture resistant

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Meets ansi c39.1 1972 standard

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0