

View Online at <https://aerobasegroup.com/nsn/6625-01-272-0918>

Circuit Current For Which Designed:

Ac and dc

Dielectric Withstanding Voltage In Volts:

700.0

Overall Depth:

0.750 inches

Overall Length:

6.500 inches

Overall Width:

1.100 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant

Indicator Type:

Digital display

Installation Design:

Hand held

Frequency Response Range:

+40.000/+500.000 hertz

Sensitivity Rating:

1.0 millivolts

Background Color:

Gray single indicator all ranges

Power Source:

Internal

Display Type:

Liquid crystal

Display Digit Quantity:

3-1/2

Measurement Range:

+0.000/+1.999 volts, dc single indicator 9th range

Scale Selection Method:

Switch

Features Provided:

Magnetic shield and overranging

Accuracy Rating:

Porm o.7 pct of reading plus 4 digits single indicator 11th range

Display Color:

Amber single indicator all ranges

Circuit Attachment Method And Quantity:

2 wire lead

Special Features:

Two batteries compartments to hold two Ir-44 button batteries made from alkaline-manganese

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Hand-held

Unit Of Issue Weight:

0.162 pounds

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0